




VIRTUAL POLYMER COMPOUNDS, LLC

10478 Ridge Road • Medina, New York 14103
Phone: 585-735-9668 • Toll Free: 888-290-9522

Fax: 585-735-9965 • www.virtualpolymercompounds.com

Administrative Office: One John James Audubon Pkwy • Amherst, NY 14228

Enduro Model 200 Insulated Equipment Enclosure



DESIGN FEATURES

- **FULLY INSULATED** The “*ENDURO*” line of fiberglass enclosures are fully insulated with 1” of polyurethane insulation yielding an R Value of 7.1. The insulation is encapsulated between two layers of fiberglass laminate.
- **MAINTENANCE FREE-** The “*ENDURO*” line of fiberglass shelters are virtually maintenance free. The exterior exposed surface is a high-grade polyester “gel coat” surface. This surface finish is especially designed to withstand UV exposure and the harshest elements. This surface also resists air born contaminants typically found at most industrial and treatment sites.
- **STRUCTURAL LOAD-** The “*ENDURO*” line of fiberglass shelters are built to meet most unified Building Codes. When properly installed the unit will withstand I-90 wind loading and live loads up to 50 psf. Simply stated, the unit will handle the winds of the mid-west and the snows of Alaska.
- **SECURE-** The “*ENDURO*” line of fiberglass Shelters includes a standard three-point door latch/lock system. Door hardware includes a keyed latch.
- **FULLY ASSEMBLED-** The “*ENDURO*” line of fiberglass shelters are shipped fully assembled and ready for installation.

TYPICAL OPTIONS

- **HEATER-** Base Board type 110 volt, 500 watt Heater with integral thermostat. Hazardous area Heater and remote thermostat are also available
- **EXHAUST FAN-** 60 CFM, 110 volt, “squire cage” type Exhaust fan with high temperature activated thermostat. Other size and type exhaust and intake fans are available. Door activated fan switch systems with thermostat lockout is available.
- **LIGHT AND SWITCH-** 60 Watt, incandescent, sealed light fixtures with plastic base assembly. Interior, exterior (weather proof) and door activated switches are available. Alarm lighting systems are available in many types and sizes
- **INTEGRAL FLOOR-** All units are available with fiberglass floor. The floor assembly is integral to the fiberglass interior wall and will serve as full containment. Floor can be smooth or have a slip resistant finish.
- **LOAD CENTER-** Standard, NEMA 3R and 4X load centers available with or without main and single pull commercial breakers.
- **WALL MOUNT PANEL -** Panel and strut can be laminated into the wall for easy and secure equipment mounting.
- **HAVE A SPECIAL NEED ?**
We can design a Shelter to meet that Need